

FEATURE

- 100% Rated Power at working temperature +125°C.
- AEC-Q200 qualified.
- Superior Anti-Surge Voltage performance.
- Superior Anti-Sulfur performance.
- RoHS complaint.
- High reliability and stability.
- Meet application requirements for high temperature and high humidity with 85°C and 85%RH.
- Applications:
 - Automotive electronics
 - Medical devices
 - Industrial control system
 - etc.

MANUFACTURER PART NO.

For example: AS1206J100KT5G00-AS1206 ±5% 100KΩ T/R-5000

Series	Size	Tol.	Value	PKG	SPQ	Feature	TCR
2 codes	4 codes	1 code	2-5 codes	1 code	1 code	1 code	2 codes
AS	1206	J	100K	T	5	G	00
Automotive Grade Anti-Sulfur Anti-Surge Thick Film Chip Resistors	0201 0402 0603 0805 1206 1210 2010 2512	F=1% J=5%	1R ^① =1Ω 4R7=4.7Ω 4K7 ^② =4.7KΩ 100K=100KΩ 4M7 ^③ =4.7MΩ	T=T/R ^④	4=4K 5=5K A=10K B=15K	G=Std. S=P.C. ^⑤	00=Refer to table as below.

Note: ① R=Radix, 10⁰, Ω

② K=Kilo, 10³, KΩ

③ M=Mega, 10⁶, MΩ

④ T/R=Taping in Reel Package type

⑤ P.C.: Personal and Customized.

CHARACTERISTIC

Type	Rated Power	MWV ^①	MOV ^②	DWV ^③	Tolerance	Value Range	Jumper(Ω)		
							Rated Current	MOC ^④	Range
AS0201	1/20W	25V	50V	/	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	0.5A	1A	50mΩ Max.
AS0402	1/16W	50V	100V	100V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	1A	2A	50mΩ Max.
AS0603	1/10W	75V	150V	300V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	1A	2A	50mΩ Max.
AS0805	1/8W	150V	300V	500V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	2A	5A	50mΩ Max.
AS1206	1/4W	200V	400V	500V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	2A	10A	50mΩ Max.
AS1210	1/3W	200V	500V	500V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	2A	10A	50mΩ Max.
AS2010	3/4W	200V	500V	500V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	2A	10A	50mΩ Max.
AS2512	1W	200V	500V	500V	±1%, ±5%	1Ω ≤ R ≤ 10MΩ	2A	10A	50mΩ Max.


Note: ① MWV=Max. Working Voltage

② MOV: Max. Overload Voltage

③ DWV: Dielectric Withstanding Voltage


④ MOC: Max. Overload Current

POWER DERATING CURVE



Note: Operating Temperature Range: -55°C ~ +155°C

PULSE DURATION CURVE



RATED VOLTAGE

Resistors should have a Rated Voltage DC or AC (RMS) corresponding to Rated Power which can be calculated by formula as below.

The Rated Voltage of certain resistance value should be the calculated result or Max. Working Voltage of product series whichever less.

Formula:

$$E = \sqrt{P \times R}$$


E=Rated voltage(V)

P=Rated power(W)

R=Nominal resistance(Ω)

DIMENSIONS

Unit: mm


Figure	Type	L	W	H	A	B
	AS0201	0.60±0.03	0.30±0.03	0.23±0.03	0.12±0.05	0.15±0.05
	AS0402	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
	AS0603	1.60±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20
	AS0805	2.00±0.15	1.25±0.15	0.55±0.10	0.40±0.20	0.40±0.20
	AS1206	3.10±0.15	1.55±0.15	0.55±0.10	0.45±0.20	0.45±0.20
	AS1210	3.10±0.10	2.60±0.20	0.55±0.10	0.50±0.25	0.50±0.20
	AS2010	5.00±0.10	2.50±0.20	0.55±0.10	0.60±0.25	0.50±0.20
	AS2512	6.35±0.10	3.20±0.20	0.55±0.10	0.60±0.25	0.50±0.20

RELIABILITY

Item	Test Method	Acceptable Criterion								
High Temperature Exposure	+155°C, 1000hrs., unpowered, measure the resistance change rate after test. Reference: AEC-Q200 Test 3, MIL-STD-202 Method 108	1% Series: $\Delta R/R = \pm 1.0\%$ 5% Series: $\Delta R/R = \pm 2.0\%$								
Temperature Cycling	-55~+125°C, slope 10~20°C/min, dwell time 15min, 1000 cycles Reference: AEC-Q200 Test 4, JESD22 Method JA-104	$\Delta R/R = \pm 2.0\%$								
Biased Humidity	85°C, 85%RH, load 10% rated power, 1000hrs., take it out and stabilized 24 hrs. then measure the change rate of resistance value Reference: AEC-Q200 TEST 7, MIL-STD-202 Method 103	1% Series: $\Delta R/R = \pm 2.0\%$ 5% Series: $\Delta R/R = \pm 3.0\%$								
Operational Life	125°C, rated voltage (calculated according to derating curve), 1000 hrs., with cycle 90 min ON, 30 min OFF Reference: AEC-Q200 Test 8, MIL-STD -202 Method 108	1% Series: $\Delta R/R = \pm 2.0\%$ 5% Series: $\Delta R/R = \pm 3.0\%$								
Resistance to Solvent	Immerse in isopropanol solvent at room temperature (23±5°C) for 5min, wipe 10 times with a hard toothbrush, repeat 3 times, take out and blow dry for examination Reference: AEC-Q200 Test 12, MIL-STD-202 Method 215	No visible damage								
Resistance to Soldering Heat	Soak in a tin furnace at 260±5°C for 10±1 seconds, take out and stand for more than 60 minutes, then measure the change rate of resistance value. Reference: AEC-Q200 TEST 15, MIL-STD-202 Method 210	$\Delta R/R = \pm 1.0\%$								
ESD	Human body mode, two discharges, positive and negative polarity once each <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">Size</td> <td style="text-align: center;">0201</td> <td style="text-align: center;">0402, 0603</td> <td style="text-align: center;">0805 and above</td> </tr> <tr> <td style="text-align: center;">Test Voltage</td> <td style="text-align: center;">500V</td> <td style="text-align: center;">1000V</td> <td style="text-align: center;">2000V</td> </tr> </table> Reference: AEC-Q200 Test 17, AEC-Q200-002	Size	0201	0402, 0603	0805 and above	Test Voltage	500V	1000V	2000V	$\Delta R/R = \pm 2.0\%$
Size	0201	0402, 0603	0805 and above							
Test Voltage	500V	1000V	2000V							
Solderability	Pretreatment: dry heat 155°C, 4 hrs. or PCT aging for 4 hrs. (equivalent), after take out, stand at room temperature for 2 hrs. Test method: 1. Dip the resistance in a tin furnace at 245±3°C for 3 seconds, then take it out and observe the solder area under a microscope; 2. Reflow soldering test, Peak Temperature: 235°C, T=40± 5 seconds. Reference: AEC-Q200 Test 18, J-STD-002 & IEC 60115-1 11.1.4.3	Soldering coverage over 95% At the edge of terminal, the object underneath (e.g., white ceramic) shall not expose.								
Electrical Characterization	$TCR(PPM/^{\circ}C) = \frac{(R_2 - R_1)}{R_1 \times (T_2 - T_1)} \times 10^6$ R_1 : Resistance value tested at room temperature (Ω) R_2 : Resistance value tested at -55°C or +125°C T_1 : Temperature at room temperature ($^{\circ}C$) T_2 : Temperature at -55°C or +125°C Reference: AEC-Q200 Test 19, IEC 60115-1 6.2	$1\Omega \leq R \leq 10\Omega$: 0201: -100~+350 PPM/ $^{\circ}C$ 0402~2512: ± 200 PPM/ $^{\circ}C$ $10\Omega < R \leq 10M\Omega$: 0201: ± 200 PPM/ $^{\circ}C$ 0402~2512: ± 100 PPM/ $^{\circ}C$								
Board Flex	The SMD resistance was welded to the test board and bent with the standard pressure block. After standing for 60s under the corresponding deformation condition, the change rate of resistance value of the part was tested. <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">Size</td> <td style="text-align: center;">0402, 0603, 0805</td> <td style="text-align: center;">0201, 1206, 1210</td> <td style="text-align: center;">2010, 2512</td> </tr> <tr> <td style="text-align: center;">Depth</td> <td style="text-align: center;">5mm</td> <td style="text-align: center;">3mm</td> <td style="text-align: center;">2mm</td> </tr> </table> Reference: AEC-Q200 TEST 21, AEC-Q200-005	Size	0402, 0603, 0805	0201, 1206, 1210	2010, 2512	Depth	5mm	3mm	2mm	$\Delta R/R = \pm 1.0\%$
Size	0402, 0603, 0805	0201, 1206, 1210	2010, 2512							
Depth	5mm	3mm	2mm							
Terminal Strength	Apply 1.8Kgf. external force (0402, 1 Kgf.) on the side of the part to test the solder joint adhesion of the part Reference: AEC Q200-005	No mechanical damage or peel-off of side end								
Short Time Overload	Apply 2.5 times rated voltage or maximum overload voltage (whichever is the smallest) for 5 seconds. Reference: IEC 60115-1 8.1.4.2	1% Series: $\Delta R/R = \pm 1.0\%$ 5% Series: $\Delta R/R = \pm 2.0\%$								
Mechanical shock	Half sine wave, acceleration 100g's, each three times in X, Y and Z directions, pulse width 6ms. Reference: AEC-Q200 Test 13, MIL-STD -202 Method 213	$\Delta R/R = \pm 1.0\%$								
Vibration	Frequency: 10Hz~2000Hz, acceleration: 5g's, X, Y, Z three directions, 12 cycles in each direction, a total of 36 cycles, a single cycle test for 20min. Reference: AEC-Q200 Test 14, MIL-STD -202 Method 204	$\Delta R/R = \pm 1.0\%$								
Flammability	V-0 Reference: AEC-Q200 Test 20, UL-94	Do not burn and cotton below do not ignite								
Flame retardancy	9V _{DC} to 32V _{DC} (clamp current 500A) in each increment 1V _{DC} for 1 hr. Reference: AEC-Q200 Test 24, AEC-Q200-001	1. Nonflammable 2. Do not explode 3. The temperature cannot be higher than 350°C for 10 seconds								
FOS	Put the test sample resistor in sulfur vapor, at a temperature of 105±2°C for 750hrs Reference: ASTM-B-809-95&EIA977	$\Delta R/R = \pm 4.0\%$								


SOLDERING

Lead Free IR Reflow Soldering Profile




- Top temperature should be under 260 +5/-0 °C ,10Sec.
- Reference: J-STD-020D

Lead Free Double-Wave Soldering Profile



- Suitable for 0603 above size products
- 350±10°C within 3 Sec. if soldering iron.

SOLDERING PAD



Unit: mm

Type	A	B	C
AS0201	0.3	1.0	0.4
AS0402	0.5	1.5	0.6
AS0603	0.8	2.1	0.9
AS0805	1.2	3.0	1.3
AS1206	2.2	4.2	1.6
AS1210	2.2	4.2	2.8
AS2010	3.5	6.1	2.8
AS2512	3.8	8.0	3.5

WORKING ENVIRONMENT

If user intends to use products in special environments or states (including but not limited to the following), it is necessary to approve special characteristics and reliability for the following or other application environments.

- High temperature.
- Near the sea, or corrosive gas, such as Cl₂, H₂S, NH₃, SO₂ and NO₂, etc.
- Unverified liquids, such as water, oil, chemical or organic solvent.
- Unverified resin or paint to cover products.
- Products should be washed with water soluble cleaner even if non cleaning flux.

STORAGE / CARRY CONDITIONS

- Temperature: 25±5°C
- Humidity: 60±15%RH
- Storage life:
 - 0201 size: 1 year;
 - 0402 above size: 2 years.
 - FIFO
- Please hold box correct orientation when storing and carrying. It is strictly prohibited to fall or squeeze the box, otherwise the product electrode or body may be damaged.

LEGAL DISCLAIMER

GiantOhm and its distributors or agents (hereinafter referred to as GiantOhm) shall not bear any responsibility for any error, inaccuracy or incompleteness contained in any product related information (including but not limited to product specifications, data, pictures, and charts). GiantOhm may change, revise, or improve product related information at any time without prior notice.

GiantOhm makes no commitment, guarantee for the suitability of its products for special purposes or the continuous production of any of its products. To the maximum extent permitted by law, GiantOhm does not assume any of the following responsibilities:

- A. All liabilities arising from the application or use of any GiantOhm's products.
- B. All liabilities, including but not limited to the loss of profits or direct damage, indirect damage, special damage, punitive damage, derivative damage or incidental damage caused by or related to GiantOhm's products.
- C. All implied warranties, including fitness for a particular purpose, non-infringement, and merchantability.

GiantOhm defines this product as a general consumer electronic purpose, which is not applicable to any medical lifesaving or life-sustaining equipment, nor to any application that may cause casualties in case of failure of GiantOhm's products.

All technical suggestions on product application provided by GiantOhm are provided free of charge. GiantOhm assumes no obligation and responsibility for adopting such technical suggestions and available results, and all risks of adopting such suggestions shall be borne by the buyer. All risks and responsibilities arising from the buyer's use of GiantOhm's products in combination with other materials or raw materials, or in any combination in its manufacturing process, shall be borne by the buyer, regardless of any oral or written technical instructions, suggestions or other requirements given by GiantOhm for the use of the products.

The information provided above is only to explain the product specifications. If the product is not changed, GiantOhm has all the rights to modify the above contents without prior notice, and the product change will be notified to the customer by ECN.

